

SP-12 Spray Unit

Primary uses:

- *Moulding and trim*
- *Door jambs and cabinet components*
- *Wood flooring*



Standard Features:

- Compatible with both waterborne and solvent based coatings
- Maximum part width: 12"
- Minimum part length: 36"
- Maximum line speed 150 fpm
- Must be used in a functional spray booth unless the machine is equipped with the optional exhaust system
- Fluid system with three spray guns, fluid filter, & fluid pump included
- Three adjustable gun arms
- 9'-0" long variable speed live roll conveyor w/ electric powered drive
- Pneumatic gun trigger mechanism to automatically trigger guns on/off

Optional Equipment/Features:

- Removable rollers to transfer parts across spray area (14" minimum part length)
- De-nib station mounted to infeed with choice of sanding head or nylon de-nib brush
- Stain wipe station mounted to outfeed with stain wipe brush
- Exhaust system with spray enclosure, exhaust fan, & exhaust filter system
- Conversion to pump system with individual gun regulators
- Conversion to photo eye gun trigger

Solidly constructed for long term reliability, Dubois equipment is engineered with innovations to improve productivity and minimize clean-up, maintenance and downtime.

It's manufactured in the U.S., to assure fast response and prompt availability of replacement parts from local suppliers.